

**Safety Data Sheet (SDS)**  
**According to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS**

**Section 1: Identification of the Substance/Mixture and the Company/Undertaking**

Product Name: W/R AIR DRY ENAMEL - OUTDOOR YELLOW    Product Code: 89-3505  
Continental Products, LTD    Email: info@continentalprod.com  
1150 East 222nd Street    Phone: 216-531-0710  
Euclid, OH 44117 USA

**Chemtrec: 1- 800-424-9300**  
**Chemtrec Global: 1-703-741-5970**

Product Use: FOR INDUSTRIAL USE ONLY

**Section 2: Hazard(s) Identification**

**GHS Ratings:**

Flammable liquid	4	Flash point $\geq 60^{\circ}\text{C}$ (140°F) and $\leq 93^{\circ}\text{C}$ (200°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: $\geq 2.3 < 4.0$ or persistent inflammation
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity $\geq 3$ , Iritis $> 1.5$
Mutagen	1B	Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Reproductive toxin	2	Human or animal evidence possibly with other information

**GHS Hazards**

H227	Combustible liquid
H315	Causes skin irritation
H318	Causes serious eye damage
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child

**GHS Precautions**

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P235	Keep cool
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment, see supplemental first aid information.

P362 Take off contaminated clothing and wash before reuse  
P302+P352 IF ON SKIN: Wash with soap and water  
P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing  
P308+P313 IF exposed or concerned: Get medical advice/attention  
P332+P313 If skin irritation occurs: Get medical advice/attention  
P370+P378 In case of fire: Use alcohol resistant foam, dry chemical, carbon dioxide (CO2), dry sand for extinction  
P405 Store locked up  
P403+P235 Store in a well ventilated place. Keep cool  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Manufacturer/supplier or the competent authority to specify whether disposal requirements apply to contents, container or both.

**Signal Word: Danger**



Unnecessary exposure to any chemical should be avoided. NOTICE--Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after applicable limits. Follow respirator manufacturer's directions for respirator use.

**Section 3: Composition/Information on Ingredients**

Chemical Name	CAS number	Weight Concentration %
Water	7732-18-5	46.00%
Trizinc diphosphate	7779-90-0	5.00%
2-Butoxyethanol	111-76-2	5.00%
Titanium dioxide	13463-67-7	4.00%
2-Butanol	78-92-2	3.00%
Ammonium hydroxide	1336-21-6	1.00%
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	0.20%

**Section 4: First Aid Measures**

**After Inhalation:** Immediately supply fresh air. Keep patient in restful and comfortable position for breathing. If required provide artificial respiration, although this may be dangerous. Consult doctor if symptoms persist.

**After Eye Contact:** Immediately rinse opened eye(s) for several minutes under running water. Use lukewarm water if possible. Remove contact lenses if worn. Get medical attention.

**After Skin Contact:** Remove contaminated clothing and shoes. Immediately wash with water and soap, rinse thoroughly. If skin irritation continues, consult a doctor.

**After Swallowing:** Immediately get medical attention. Call a poison center or physician. Rinse out mouth and then drink small amounts of water. Do not induce vomiting as this may be dangerous. Aspiration hazard if swallowed,

can enter lungs and cause damage. If vomiting occurs, the head should be kept low to avoid vomit entering the lungs. Maintain an open airway.

**Notes to Physician:** Treat symptomatically.

## Section 5: Firefighting Measures

Flash Point: 63 C (145 F)

LEL: 1.00

UEL:

### Extinguishing Media:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

### Special Hazards Arising from the Substance of Mixture:

Formation of toxic gases is possible during heating or in case of fire. Check flammability in section 2 of this sheet.

Mixture in sealed and heated containers may cause explosion hazard.

Spray booth filters, rags, and clean-up materials may spontaneously combust if exposed to air while drying.

### Hazardous Combustion Products may include the following:

Carbon oxides. Metal oxide(s). Nitrogen oxides.

Vapors are heavier than air and may spread along floors. Vapors may travel considerable distance to source of ignition and flash back.

### Advice for Firefighters:

Clear fire area of unprotected personnel. Containers that are exposed to intense heat should be cooled with water.

Avoid spreading burning liquid with the water used for cooling purposes. Do not enter fire area without protective gear. Fight fire from safe distance or a protected location.

### Fire Equipment:

Wear self-contained respiratory protective device. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## Section 6: Accidental Release Measures

### Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Wear protective clothing.

Keep from contacting skin or eyes.

Avoid breathing vapors, mist, or gas.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

If any equipment is necessary, ensure that it is non-sparking and electrically-protected.

### Environmental precautions:

Do not allow product to reach sewage system or any water source.

In case of seepage into the ground inform responsible authorities

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep contaminated washing water and dispose of appropriately

### Methods and material for containment and cleaning up:

Ensure adequate ventilation

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste.  
 Do not flush with water or aqueous cleansing agents.  
 Send for recovery or disposal in suitable receptacles according to local, state and federal regulations.

## Section 7: Handling and Storage

### Handling:

Apply proper ventilation, possibly combined with local exhaust.  
 Do not eat, smoke or drink during use.  
 For personal protection see Section 8.  
 Keep away from sources of ignition.  
 Keep material out of reach of children.  
 Wash thoroughly after handling.

### Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges by bonding and grounding product containers before and during material transfers. Keep respiratory protective device available.  
 Dispose of filters, waste, rags and clean-up materials in closed, airtight containers.

### Conditions for safe storage, including any incompatibilities:

#### Storage:

Keep away from sources of ignition - no smoking. Store in a cool, well ventilated place. Keep in original, closed packaging. Comply with governmental regulations.  
 Keep container tightly closed. Store out of direct sunlight, between 40 and 90F.

**Specific end use(s):** For professional use only.

## Section 8: Exposure Controls/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Water 7732-18-5	Not Established	Not Established	Not Established
Trizinc diphosphate 7779-90-0	Not Established	Not Established	Not Established
2-Butoxyethanol 111-76-2	50 ppm TWA; 240 mg/m3 TWA	20 ppm TWA	NIOSH: 5 ppm TWA; 24 mg/m3 TWA
Titanium dioxide 13463-67-7	15 mg/m3 TWA (total dust)	10 mg/m3 TWA	Not Established
2-Butanol 78-92-2	150 ppm TWA; 450 mg/m3 TWA	100 ppm TWA	NIOSH: 100 ppm TWA; 305 mg/m3 TWA 150 ppm STEL; 455 mg/m3 STEL
Ammonium hydroxide 1336-21-6	TWA 25.00 ppm 18.00 mg/m3	TWA 25.00ppm STEL 35.00 ppm	Not Established
Distillates, petroleum, solvent-dewaxed heavy paraffinic 64742-65-0	Not Established	Not Established	Not Established

### Ventilation:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits .

#### **Personal Protective Equipment/General Protective and Hygienic Measures:**

##### **Respiratory Protection:**

In outdoor or open areas use (NIOSH/MSHA approved) mechanical filter respirator to remove solid airborne particles of overspray during spray application. In restricted ventilation areas use (NIOSH/MSHA approved) chemical-mechanical filters designed to remove a combination of particulate and gas and vapor. In confined areas use (NIOSH/MSHA approved) airline type respirators or hoods. Respiratory protection may also be necessary in any later manufacturing operations in which the product may become airborne in the form of vapor or dust.

##### **Protective Gloves:**

Protective gloves are required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact. (Consult your safety equipment supplier.)

##### **Eye Protection:**

Avoid contact with eyes. Wear goggles if there is a likelihood of contact with eyes. (Consult your safety equipment supplier.) Eyewash stations and safety showers should be readily available in use and handling areas. Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

##### **Body Protection:**

Chemically resistance gloves, apron and safety goggles are recommended. Type of protective equipment should be selected based on concentration amount and conditions of use of this material.

##### **Contaminated Gear:**

Dispose of in accordance with official regulations .

### **Section 9: Physical and Chemical Properties**

<b>Boiling Range 100 to 3000 °C</b> <b>Coating VOC (as supplied) 0.78</b> <b>lb/gl</b>	<b>Specific Gravity (SG) 1.157</b> <b>Coating VOC (EPA 1.72</b> <b>calculation) lb/gl</b>
--	---

### **Section 10: Stability and Reactivity**

#### **Product Stability:**

Product is stable under normal circumstances.

#### **Incompatibilities:**

Avoid contact with strong oxidizing agents.

#### **Hazardous Decomposition:**

Thermal decomposition may form toxic materials; carbon dioxide, carbon monoxide, etc. Thermal decomposition may form toxic materials; carbon dioxide, carbon monoxide, various hydrocarbons, etc.

Hazardous polymerization will not occur.

### **Section 11: Toxicological Information**

#### **Mixture Toxicity**

Dermal Toxicity LD50: 2,075mg/kg

**Component Toxicity**

111-76-2

2-Butoxyethanol

Oral LD50: 470 mg/kg (Rat) Dermal LD50: 99 mg/kg (Rabbit) Inhalation LC50: 450 ppm (Rat)

**Routes of Entry:**

No data available.

**Target Organs:**

Blood System    Eyes    Kidneys    Liver    Central Nervous System    Skin    Respiratory

**Effects of Overexposure**

**Carcinogenicity:**

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64742-65-0	Distillates, petroleum, solvent-dewaxed heavy paraffinic	0.2	Distillates, petroleum, solvent-dewaxed heavy paraffinic: EU REACH: Present (L)

**Section 12: Ecological Information**

**Environmental Impact Statement/Toxicity:**

- Aquatic toxicity:** No further relevant information available
- Persistence and degradability:** No further relevant information available
- Bioaccumulative potential:** No further relevant information available.
- Mobility in soil:** No further relevant information available.
- Other adverse effect:** No further relevant information available

**Component Ecotoxicity**

Trizinc diphosphate	LC50 - Oncorhynchus mykiss (rainbow trout) - 0.09 mg/l - 96.0 h
2-Butoxyethanol	96 Hr LC50 Lepomis macrochirus: 1490 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 2950 mg/L 48 Hr EC50 Daphnia magna: >1000 mg/L
2-Butanol	96 Hr LC50 Pimephales promelas: 3380 - 3990 mg/L [flow-through] 48 Hr EC50 Daphnia magna: 1859 - 7143 mg/L [Static]
Ammonium hydroxide	96 Hr LC50 Pimephales promelas: 8.2 mg/L 48 Hr EC50 water flea: 0.66 mg/L; 48 Hr EC50 Daphnia pulex: 0.66 mg/L
Distillates, petroleum, solvent-dewaxed heavy paraffinic	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L 48 Hr EC50 Daphnia magna: >1000 mg/L

**Section 13: Disposal Considerations**

**Waste treatment methods:**

**Recommendation:**

Must not be disposed of together with household garbage.  
Do not allow product to reach sewage system.

Spray booth filters, rags, and clean-up materials may spontaneously combust if exposed to air while drying. These materials should be stored in closed metal or water-filled containers.

Disposal of this product and any by-products must at all times comply with local, state and Federal regulations for hazardous wastes. All entities that store, transport or handle hazardous waste must take the necessary measures to

prevent risks of pollution, release into the environment or damage to people and animals.

**Contaminated Packaging:**

Waste packaging should be recycled. Care should be taken when handling emptied containers that have not been cleaned. Empty containers retain some product residues. Vapor from that residue may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers.

**Section 14: Transport Information**

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Not Regulated			

**Section 15: Regulatory Information**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Prop 65 - Chemicals Known to Cause Developmental Toxicity  
- None

Prop 65 - Chemicals Known to Cause Cancer:  
- None

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

TSCA (Toxic Substances Control Act)  
- None

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
USA	Inventory - United States - Section 8(b) Inventory (TSCA)	Yes
Canada	DSL (Canadian Domestic Substance List)	Yes
Europe	EINECS (European Inventory of Existing Commercial Chemicals)	No

**EU Risk Phrases**

**Safety Phrase**

- None

**Section 16: Other Information**

**\*DISCLAIMER\***

**THE INFORMATION CONTAINED HEREIN WAS RECEIVED FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCES. CONTINENTAL PRODUCTS MAKES NO EXPRESS OR IMPLIED WARRANTIES REGARDING THE ACCURACY OF THE ABOVE INFORMATION AND YOU SHOULD NOT RELY ON IT. YOU SHOULD TEST THIS PRODUCT FOR CHEMICAL COMPOSITION AND CONSULT APPLICABLE SAFETY AND MEDICAL STANDARDS AND PROFESSIONALS RELATED THERETO. CONTINENTAL PRODUCTS DOES NOT WARRANT THE SUITABILITY OF THE PRODUCT FOR ANY APPLICATION BY THE USER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.**

Date revised: 2019-01-25

Reviewer Revision 1

Date Prepared: 1/28/2019