

Gorbel Outdoor Yellow

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Gorbel Outdoor Yellow
Common Name: Paint Aerosol
SDS Number: 81321
Revision Date: 2/6/2025
Chemical Formula: 81321
Product Description: Paint Aerosol
Product Use: Spray Paint
Instructions: Use in a well ventilated area. Do not use or store near heat or open flame.
Supplier Details: Premier Aerosol Packaging, Inc.
7777 Hub Parkway
Valley View, OH 44125
Phone: 216-674-1590
Email: sds@premieraerosol.com
Web: www.premieraerosol.com
Emergency: 1-800-535-5053 Infotrac

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1
Physical, Gases Under Pressure, Liquefied Gas
Health, Aspiration hazard, 1
Health, Serious Eye Damage/Eye Irritation, 2 A
Health, Specific target organ toxicity - Single exposure, 3
Health, Carcinogenicity, 2
Health, Specific target organ toxicity - Repeated exposure, 2
Health, Reproductive toxicity, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H304 - May be fatal if swallowed and enters airways
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure
H361 - Suspected of damaging fertility or the unborn child

GHS Precautionary Statements:

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. No smoking
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapours/spray.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing should not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 IF SWALLOWED: Immediately call a POISON CENTER or doctor
 IF ON SKIN: Gently wash with plenty of soap and water.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/ attention.
 Call a POISON CENTER or doctor/physician if you feel unwell.
 Get medical advice/attention if you feel unwell.
 Do NOT induce vomiting.
 If eye irritation persists: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 Dispose of contents/container in accordance with all local, regional, national and international regulations

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

3

COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients

CAS#	%	Chemical Name
67-64-1	40-50%	Acetone
108-88-3	10-20%	Toluene
123-86-4	10-20%	n-Butyl acetate
68476-86-8	25-35%	Propane/ Isobutane
96-29-7	<.1%	Methyl ethyl ketoxime
100-42-5	<.1%	Styrene
64742-88-7	<.1%	Medium aliphatic naphtha
67-56-1	<.1%	Methanol
71-36-3	<.5%	1-Butanol

4

FIRST AID MEASURES

If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. Give oxygen or artificial respiration if needed. Get immediate medical attention.

Inhalation:

Wash with soap and water. Remove contaminated clothing immediately. Remove contaminated clothing and wash before reuse. Promptly flush skin with water until all chemical is removed. Get medical attention if needed.

Skin Contact:

Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Flush with large amounts of water. Get immediate medical attention.

Eye Contact:

Call a poison center or physician. Rinse mouth with water. Seek immediate medical attention. Do not induce vomiting.

Ingestion:

General Advice: Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

Flash Point: Flash point -60 C (-73F)

LEL: 1.0

UEL: 16

Extinguishing Media:

Dry powder, foam, carbon dioxide is recommended. Water spray may be on structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

Special Fire Fighting Procedures:

At elevated temperatures formation of toxic gases is possible during heating or in case of fire. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Vapors may be heavier than air and may travel along the ground before ignition/flashing back to vapor source. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Materials will float, avoid spreading the fire.

Unusual Fire & Explosion Hazards:

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are cooled in a fire, they may rupture and ignite.

Spill or Leak Instructions:

Contain spill with dikes of soil or non-flammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using nonflammable absorbent or flushing sparingly with water. Contain large spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not involve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

Handling Precautions: Handling: FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN

Do not puncture, incinerate or drop containers. Handle in accordance with good industrial hygiene and safety practices. Ensure adequate ventilation. Avoid breathing vapors or mist. Avoid contact with eyes, skin, or clothing. Wash thoroughly after handling. Wash clothing before reuse and decontaminate or discard contaminated shoes. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Storage Requirements: Conditions for safe storage, including any incompatibilities:

Store in cool/dry area. Keep away from direct sunlight. Keep away from heat, sparks, and flames. Keep container closed when in use. Store away from incompatible materials and ignition sources. Product should be stored below 120 F.

Incompatible Products: Strong oxidizing agents

Personal Protective Equipment: HMIS PP, G | Safety Glasses, Gloves, Vapor Respirator

Hygiene Measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Acetone cas#:(67-64-1) [15-40%]

Components with workplace control parameters

TWA 500 ppm USA. ACGIH Threshold Limit Values (TLV)

Eye & Upper Respiratory Tract irritation
Central Nervous System impairment
Hematologic effects

Not classifiable as a human carcinogen

Not classifiable as a human carcinogen

Not classifiable as a human carcinogen

TWA 150 ppm USA. ACGIH Threshold Limit Values (TLV)
Eye & Upper Respiratory Tract irritation

STEL 200 ppm USA. ACGIH Threshold Limit Values (TLV)
Eye & Upper Respiratory Tract irritation

TWA 150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
710 mg/m3 1910.1000

STEL 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
950 mg/m3 1910.1000

TWA 150 ppm USA. Occupational Exposure Limits (OSHA) - Table Z- 1
710 mg/m3 Limits for Air Contaminants
The value in mg/m3 is approximate.

TWA 150 ppm USA. NIOSH Recommended Exposure Limits
710 mg/m3

ST 200 ppm USA. NIOSH Recommended Exposure Limits
950 mg/m3

Propane cas#:(74-98-6) [10-20%]

Components with workplace control parameters

TWA 1,000 ppm USA. ACGIH Threshold Limit Values
(TLV)
Central Nervous System impairment
Cardiac sensitization

TWA 1,000 ppm USA. Occupational Exposure Limits
1,800 mg/m3 (OSHA) - Table Z-1 Limits for Air
Contaminants
The value in mg/m3 is approximate.

TWA 1,000 ppm USA. OSHA - TABLE Z-1 Limits for
1,800 mg/m3 Air Contaminants - 1910.1000

TWA 1,000 ppm USA. NIOSH Recommended
1,800 mg/m3 Exposure Limits

Methyl ethyl ketone cas#:(78-93-3) [1-5%]

Propanoic acid, 3-ethoxy-, ethyl ester cas#:(763-69-9) [.1-1.0%]

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Opaque Yellow Liquid

Physical State: Liquid

Spec Grav./Density: .75

Boiling Point: -44F(-42C)

Partition Coefficient: Not determined

Vapor Pressure: Not determined

pH: No data available

Evap. Rate: Faster than Ether 5.7

Odor: Solvent

Solubility: Not Water Soluble

Freezing/Melting Pt.: No data available

Flash Point: -60C (-73F)

Vapor Density: Heavier than Air 5.0
EFT Coating 2.05 MIR(Federal)/ 1.20

VOC: MIR(CA)

Auto-Ignition Temp: Not determined

UFL / LFL: 16/1

Reactivity:	No specific test data related to reactivity available for this product or its ingredients.
Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Materials to Avoid:	Strong Oxidizing Agents.
Hazardous Decomposition:	Combustion will produce carbon dioxide and, possibly toxic chemicals such as carbon monoxide.
Hazardous Polymerization:	Will not occur.

Acetone cas#:(67-64-1) [40-50%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 5,800 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Tremor.

LC50 Inhalation - rat - 8 h - 50,100 mg/m3

Inhalation: no data available

LD50 Dermal - guinea pig - 7,426 mg/kg

Skin corrosion/irritation: Skin - rabbit Result: Mild skin irritation - 24 h

Serious eye damage/eye irritation: Eyes - rabbit Result: Eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence

Toluene cas#:(108-88-3) [10-20%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - > 5,580 mg/kg

LC50 Inhalation - rat - 4 h - 12,500 - 28,800 mg/m3

LD50 Dermal - rabbit - 12,196 mg/kg

no data available

Skin corrosion/irritation: Skin - rabbit Result: Skin irritation - 24 h

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: rat Liver DNA damage

Carcinogenicity:

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Toluene)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: Damage to fetus possible Suspected human reproductive toxicant

Reproductive toxicity - rat - Inhalation:

Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count).

Experiments have shown reproductive toxicity effects in male and female laboratory animals.

Developmental Toxicity - rat - Oral:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: XS5250000

Lung irritation, chest pain, pulmonary edema, Inhalation studies on toluene have demonstrated the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals.

Stomach - Irregularities - Based on Human Evidence

n-Butyl acetate cas#:(123-86-4) [10-20%]

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - 10,700 - 14,130 mg/kg

Inhalation LC50 LC50 Inhalation - rat - 4 h - > 21.0 mg/l

Dermal LD50 LD50 Dermal - rabbit - 17,600 mg/kg

Other information on acute toxicity no data available

Skin corrosion/irritation: Skin - rabbit - Skin irritation - 24 h

Serious eye damage/eye irritation: Eyes - rabbit - Moderate eye irritation

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: Developmental Toxicity - rat - Inhalation:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). Specific Developmental Abnormalities: Musculoskeletal system.

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):
May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: Drowsiness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

RTECS: AF7350000

Styrene cas#:(100-42-5) [<.1%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 2,650 mg/kg Remarks: Behavioral:Somnolence (general depressed activity). Liver:Other changes.

LC50 Inhalation - rat - 4 h - 12,000 mg/m3

Dermal: no data available

Skin corrosion/irritation: Skin - rabbit Result: Skin irritation

Serious eye damage/eye irritation: Eyes - rabbit Result: Eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: Laboratory experiments have shown mutagenic effects.

Carcinogenicity:

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Styrene)

NTP: Reasonably anticipated to be a human carcinogen (Styrene)

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: WL3675000

Dermatitis, Central nervous system depression, Nausea, Dizziness, Headache
Endocrine system. -

Acetone cas#:(67-64-1) [40-50%]

Information on ecological effects

Toxicity: no data available

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 13,500.00 mg/l - 48 h.
other aquatic invertebrates

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Toluene cas#:(108-88-3) [10-20%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 7.63 mg/l - 96 h.

NOEC - Pimephales promelas (fathead minnow) - 5.44 mg/l - 7 d

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 8.00 mg/l - 24 h.
other aquatic invertebrates

Immobilization EC50 - Daphnia magna (Water flea) - 6 mg/l - 48 h

Toxicity to algae EC50 - Chlorella vulgaris (Fresh water algae) - 245.00 mg/l - 24 h.

EC50 - Pseudokirchneriella subcapitata (green algae) - 10.00 mg/l - 24 h

Persistence and degradability: Biodegradability Result: - Readily biodegradable.

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

n-Butyl acetate cas#:(123-86-4) [10-20%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Lepomis macrochirus (Bluegill) - 100 mg/l - 96 h.

Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 72.8 - 205.0 mg/l - 24 h.
and other aquatic invertebrates

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.
no data available

Styrene cas#:(100-42-5) [<.1%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Leuciscus idus (Golden orfe) - 17.00 - 66.00 mg/l - 48 h.
NOEC - Pimephales promelas (fathead minnow) - 4 mg/l - 96 h
LC50 - Pimephales promelas (fathead minnow) - 4.08 mg/l - 96 h
LOEC - Pimephales promelas (fathead minnow) - 7.6 mg/l - 96 h
Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 182.00 mg/l - 24 h.
other aquatic invertebrates
NOEC - Daphnia magna (Water flea) - 1.9 mg/l - 48 h
LOEC - Daphnia magna (Water flea) - 3.3 mg/l - 48 h
EC50 - Daphnia magna (Water flea) - 4.7 mg/l - 48 h

Persistence and degradability: Biodegradability aerobic - Exposure time 28 d Result: > 60 % - Readily biodegradable.

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

no data available

13

DISPOSAL CONSIDERATIONS

Waste treatment methods

Product: Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging: Dispose of as unused product.

Dispose of in accordance with local regulations. Recommendation: consultation with the disposal agency and the relevant authorities

14

TRANSPORT INFORMATION

DOT

Proper Shipping Name: Aerosols (limited quantity)
Class: 2.1
ERG:126

TDG

UN-Number :UN1950
Proper Shipping Name: Aerosols (limited quantity)
Class: 2.1
Description: UN1950, Aerosols,2.1

MEX

UN-Number :UN1950
Proper Shipping Name: Aerosols(limited Quantity)
Class: 2.1
Description: UN1950, Aerosols,2.1

IATA

UN-Number :ID8000
Proper Shipping Name: Consumer Commodity
Hazard Class: 9
ERG Code: 9L
Description: ID8000, Consumer commodity, 9
Authorization: Limited Quantity
Packing 1900

IMDG/IMO
UN-Number: UN1950
Proper Shipping Name: Aerosols(Limited Quantity)
Hazard Class: 2
Subsidiary Class: See SP63
EmS No.: F-D, S-U
Description: UN1950, Aerosols, 2.1(see SP63)

15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

RQ(5000LBS), Acetone (67-64-1) [40-50%] CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

RQ(1000LBS), Toluene (108-88-3) [10-20%] CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, PRIPOL, PROP65, SARA313, TOXICPOL, TOXICRCRA, TSCA, TXAIR, TXHWL

RQ(5000LBS), n-Butyl acetate (123-86-4) [10-20%] CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR

Propane/ Isobutane (68476-86-8) [25-35%] TSCA

Methyl ethyl ketoxime (96-29-7) [<.1%] TSCA, TXAIR

Styrene (100-42-5) [<.1%] CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, NRC, OSHAWAC, PA, SARA313, TSCA, TXAIR

Medium aliphatic naphtha (64742-88-7) [<.1%] TSCA

RQ(5000LBS), Methanol (67-56-1) [<.1%] CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

RQ(5000LBS), 1-Butanol (71-36-3) [<.5%] CERCLA, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL



WARNING


This product can expose you to chemicals including Styrene, which is known to the State of California to cause cancer, and Toluene, and Methanol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Regulatory CODE Descriptions


RQ = Reportable Quantity
CERCLA = Superfund clean up substance
HAP = Hazardous Air Pollutants
MASS = MA Massachusetts Hazardous Substances List
NJHS = NJ Right-to-Know Hazardous Substances
OSHAWAC = OSHA workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals
TOXICRCRA = RCRA Toxic Hazardous wastes (U-List)
TSCA = Toxic Substances Control Act
TXAIR = TX Air Contaminants with Health Effects Screening Level
TXHWL = TX Hazardous waste List
CSWHS = Clean water Act Hazardous substances
EPCRAWPC = EPCRA water Priority Chemicals
PRIPOL = Clean water Act Priority Pollutants
PROP65 = CA Prop 65
TOXICPOL = Clean water Act Toxic Pollutants
NRC = Nationally Recognized Carcinogens

16 OTHER INFORMATION

NFPA:HMIS Health = 2, Fire = 4, Reactivity = 1, Specific Hazard = n/a
III:HMIS Health = 2, Fire = 4, Physical Hazard = 1
PPE: G - Safety Glasses, Gloves, Vapor Respirator



HMIS	
HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	1
PERSONAL PROTECTION	G



General Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet

Revision Date: 2/6/2025
Print Date: 02/06/2025